



**SILVYN® KLIICK GPZ-M**



**Benefits**

- Fast assembly
- Easy to disassemble
- Additional cable strain relief
- Additional cable seal

**Application range**

- In combination with protective cable conduit:
- SILVYN® RILL PA 6
- SILVYN® RILL PA 12
- Robot building
- Used in areas where cables require additional strain relief and sealing

**Norm references / approvals**

- UL FILENUMBER E308201

**Design**

- Metric connection thread
- Cable gland
- Basic body with inner seal
- Upper part with snap-in sleeve

**Suitable conduits**

- SILVYN® RILL PA 6 Page [P1154]
- SILVYN® RILL PA 12 Page [P1155]

**Technical data**

	<b>Classification</b> ETIM 5.0 Class-ID: EC001176 ETIM 5.0 Class-Description: Gland for corrugated plastic hose
	<b>Colour delivered</b> Grey RAL 7001 Black RAL 9005, UV-resistant
	<b>Material</b> PA6
	<b>Protection rating</b> IP 68 IP 69 according to DIN 40050 T.9
	<b>Temperature range</b> -40°C to +115°C

Article number	Metric size	Clamping range in mm	SW mm	Thread length mm	Clear width (mm)	For conduit with outer Ø (mm)	Suitable for SILVYN® RILL	Pieces / PU
<b>SILVYN® KLIICK, GPZ-M grey</b>								
55500800	12 x 1.5	4.0 - 6.5	16.0	8.0	6.5	10.0	10	20.0
55500810	16 x 1.5	5.0 - 9.5	18.0	8.0	9.5	13.0	1 - 3	20.0
55500820	20 x 1.5	8.0 - 12.0	24.0	8.0	13.0	15.8	16	20.0
55500830	25 x 1.5	11.0 - 16.0	27.0	8.0	16.0	21.2	21	10.0
55500840	32 x 1.5	15.0 - 21.0	34.0	10.0	18.0	28.5	28	10.0
55500850	40 x 1.5	16.0 - 26.0	40.0	10.0	25.0	34.5	34	10.0
55500860	50 x 1.5	27.0 - 35.0	55.0	12.0	32.0	42.5	42	10.0
55500870	63 x 1.5	32.0 - 42.0	65.0	12.0	44.0	54.5	54	10.0
<b>SILVYN® KLIICK, GPZ-M black</b>								
55500805	12 x 1.5	4.0 - 6.5	16.0	8.0	6.5	10.0	10	20.0
55500815	16 x 1.5	5.0 - 9.5	18.0	8.0	9.5	13.0	1 - 3	20.0
55500825	20 x 1.5	8.0 - 12.0	24.0	8.0	13.0	15.8	16	20.0
55500835	25 x 1.5	11.0 - 16.0	27.0	8.0	16.0	21.2	21	10.0
55500845	32 x 1.5	15.0 - 21.0	34.0	10.0	18.0	28.5	28	10.0
55500855	40 x 1.5	16.0 - 26.0	40.0	10.0	25.0	34.5	34	10.0
55500865	50 x 1.5	27.0 - 35.0	55.0	12.0	32.0	42.5	42	10.0
55500875	63 x 1.5	32.0 - 42.0	65.0	12.0	44.0	54.5	54	10.0

Photographs are not to scale and do not represent detailed images of the respective products.