



SILVYN® KLICK PG



Benefits

- Fast assembly
- Easy to disassemble
- Highly tensile
- High sealing performance
- Can be rotated

Application range

- In combination with protective cable conduit:
- SILVYN® RILL PA 6
- SILVYN® RILL PA 12
- Robot building

- Rotating applications

Norm references / approvals

- UL FILENUMBER E308201

Design

- PG connection thread
- Basic body with inner seal
- Upper part with snap-in sleeve

Suitable conduits

- SILVYN® RILL PA 6 Page [P1154]
- SILVYN® RILL PA 12 Page [P1155]

Technical data

	Classification ETIM 5.0 Class-ID: EC001176 ETIM 5.0 Class-Description: Gland for corrugated plastic hose
	Colour delivered Grey RAL 7001 Black RAL 9005, UV-resistant
	Material PA6
	Protection rating IP 68 IP 69 according to DIN 40050 T.9
	Temperature range -40°C to +115°C

Article number	PG size	SW mm	Total length mm	Thread length mm	Clear width (mm)	For conduit with outer Ø (mm)	Suitable for SILVYN® RILL	Pieces / PU
SILVYN® KLICK PG grey								
61800860	7	16.0	32.5	10.0	7.0	10.0	10	50.0
61800870	9	18.0	35.0	10.0	10.0	13.0	1 - 3	50.0
61800880	11	21.0	37.0	10.0	12.5	15.8	16	50.0
61800850	13.5	24.0	43.0	13.0	13.5	18.5	18	50.0
61800890	16	27.0	46.0	13.0	17.0	21.2	21	50.0
61800900	21	34.0	48.5	13.0	23.5	28.5	28	25.0
61800910	29	40.0	53.5	14.5	30.0	34.5	34	25.0
61800920	36	60.0	76.0	17.0	36.0	42.5	42	25.0
61800930	48	70.0	88.0	17.0	47.5	54.5	54	10.0
SILVYN® KLICK PG black								
61800865	7	16.0	32.5	10.0	7.0	10.0	10	50.0
61800875	9	18.0	35.0	10.0	10.0	13.0	1 - 3	50.0
61800885	11	21.0	37.0	10.0	12.5	15.8	16	50.0
61800855	13.5	24.0	43.0	13.0	13.5	18.5	18	50.0
61800895	16	27.0	46.0	13.0	17.0	21.2	21	50.0
61800905	21	34.0	48.5	13.0	23.5	28.5	28	25.0
61800915	29	40.0	53.5	14.5	30.0	34.5	34	25.0
61800925	36	60.0	76.0	17.0	36.0	42.5	42	25.0
61800935	48	70.0	88.0	17.0	47.5	54.5	54	10.0

Photographs are not to scale and do not represent detailed images of the respective products.