



**SILVYN® K-EM**



**Benefits**

- Easy to assemble
- High temperature resistance
- Cable damage can be prevented
- Additional sealing

**Application range**


- In combination with protective cable conduit:


- SILVYN® RILL PA 6
- SILVYN® RILL PA 12
- Transition or end sleeve


**Suitable conduits**


- SILVYN® RILL PA 6 Page [P1154]
- SILVYN® RILL PA 12 Page [P1155]

**Technical data**

**Classification**  
 ETIM 5.0 Class-ID: EC000519  
 ETIM 5.0 Class-Description: Terminal sleeve for protective conduits

**Colour delivered**  
 Grey RAL 7001  
 Black RAL 9005, UV-resistant

**Material**  
 TPE-V

**Temperature range**  
 -40°C to +120°C

Article number	Nominal size	Total length mm	For conduit with outer Ø (mm)	Pieces / PU
<b>SILVYN® K-EM grey</b>				
65500200	10	29.0	10.0	50.0
65500210	13	32.5	13.0	50.0
65500220	16	36.5	15.8	50.0
65500230	21	37.5	21.2	50.0
65500240	28	40.2	28.5	25.0
65500250	34	44.2	34.5	25.0
65500260	42	46.0	42.5	25.0
65500270	54	52.0	54.5	10.0
<b>SILVYN® K-EM black</b>				
65500205	10	29.0	10.0	50.0
65500215	13	32.5	13.0	50.0
65500225	16	36.5	15.8	50.0
65500235	21	37.5	21.2	50.0
65500245	28	40.2	28.5	25.0
65500255	34	44.2	34.5	25.0
65500265	42	46.0	42.5	25.0
65500275	54	52.0	54.5	10.0

Photographs are not to scale and do not represent detailed images of the respective products.